



PRODUCT CATALOG · 20–200 KW

CAT OLYMPIAN GENERATORS

Commercial gas & diesel generator sets — 27 models with full specifications and ratings.

Call **+1 (305) 984-9255**

GAS · NG / LPG

OLYMPIAN OG20

20^{KW}

3.6L NA Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	20 kW
NG / LPG	20 / 20 kW
Engine	3.6L NA Inline
Displacement	3.6 L
Aspiration	Naturally aspirated
Fuel · 100%	303 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	59 sKVA
Dimensions	77"×51"×60"
Dry weight	1,463 lb

GAS · NG / LPG

OLYMPIAN OG25

25^{KW}

3.6L NA Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	25 kW
NG / LPG	25 / 25 kW
Engine	3.6L NA Inline
Displacement	3.6 L
Aspiration	Naturally aspirated
Fuel · 100%	362 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	78 sKVA
Dimensions	77"×51"×60"
Dry weight	1,463 lb

GAS · NG / LPG

OLYMPIAN OG30

30^{KW}

3.6L NA Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	30 kW
NG / LPG	30 / 30 kW
Engine	3.6L NA Inline
Displacement	3.6 L
Aspiration	Naturally aspirated
Fuel · 100%	439 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	96 sKVA
Dimensions	77"×51"×60"
Dry weight	1,534 lb

GAS · NG / LPG

OLYMPIAN OG35

35^{KW}

3.6L NA Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	35 kW
NG / LPG	35 / 35 kW
Engine	3.6L NA Inline
Displacement	3.6 L
Aspiration	Naturally aspirated
Fuel · 100%	548 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	133 sKVA
Dimensions	77"×51"×60"
Dry weight	1,570 lb

GAS · NG / LPG

OLYMPIAN OG40

40_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	40 kW
NG / LPG	40 / 40 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	532 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	149 sKVA
Dimensions	93"×47"×55"
Dry weight	1,986 lb

GAS · NG / LPG

OLYMPIAN OG45

45_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	45 kW
NG / LPG	45 / 45 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	602 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	149 sKVA
Dimensions	93"×47"×55"
Dry weight	1,986 lb

GAS · NG / LPG

OLYMPIAN OG50

50_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	50 kW
NG / LPG	50 / 50 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	674 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	202 sKVA
Dimensions	93"×47"×55"
Dry weight	2,416 lb

GAS · NG / LPG

OLYMPIAN OG60

60_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	60 kW
NG / LPG	60 / 60 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	819 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	202 sKVA
Dimensions	93"×47"×55"
Dry weight	2,416 lb

GAS · NG / LPG

OLYMPIAN OG70

70_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	70 kW
NG / LPG	70 / 61 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	928 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	224 sKVA
Dimensions	93"×47"×55"
Dry weight	2,416 lb

GAS · NG / LPG

OLYMPIAN OG80

80_{KW}

3.6L TCAC Inline · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	80 kW
NG / LPG	80 / 61 kW
Engine	3.6L TCAC Inline
Displacement	3.6 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	1037 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	240 sKVA
Dimensions	93"×47"×55"
Dry weight	2,416 lb

GAS · NG / LPG

OLYMPIAN OG100

100 KW

6.2L V8 TCAC · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	100 kW
NG / LPG	100 / 89 kW
Engine	6.2L V8 TCAC
Displacement	6.2 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	1255 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	349 sKVA
Dimensions	96"×51"×57"
Dry weight	3,007 lb
Sound @ 7 m	70–75 dBA

GAS · NG / LPG

OLYMPIAN OG125

125 KW

6.2L V8 TCAC · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	125 kW
NG / LPG	125 / 117.9 kW
Engine	6.2L V8 TCAC
Displacement	6.2 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	1543 CFH
1φ voltage	240/120, 480/277
3φ voltage	240/120, 240/139, 208/120, 600/346
Motor start	349 sKVA
Dimensions	96"×51"×57"
Dry weight	3,226 lb
Sound @ 7 m	70–75 dBA

GAS · NG / LPG

OLYMPIAN OG150

150 KW

9.1L V8 TCAC · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	150 kW
NG / LPG	150 / 132.6 kW
Engine	9.1L V8 TCAC
Displacement	9.1 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	1769 CFH
3φ voltage	480/277, 240/120, 240/139, 208/120, 600/346
Motor start	513 sKVA
Dimensions	114"×55"×68.3"
Dry weight	3,653 lb
Sound @ 7 m	70–75 dBA

GAS · NG / LPG

OLYMPIAN OG175

175 KW

10.3L V8 TCAC · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110



SPECIFICATIONS

Standby	175 kW
NG / LPG	175 / 144 kW
Engine	10.3L V8 TCAC
Displacement	10.3 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	2145 CFH
3φ voltage	480/277, 240/120, 240/139, 208/120, 600/346
Motor start	629 sKVA
Dimensions	117.5"×63"×72"
Dry weight	3,924 lb
Sound @ 7 m	70–75 dBA

GAS · NG / LPG

OLYMPIAN OG200

200 KW

10.3L V8 TCAC · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz natural gas or propane generator set with 24-hour UL listed integral fuel tank
- Emergency Standby, Demand Response and Prime Ratings Available
- EPA Certified for Non-Emergency Application
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 Temp Rise Alternator
- UL2200, NFPA 110

SPECIFICATIONS

Standby	200 kW
NG / LPG	200 / 144 kW
Engine	10.3L V8 TCAC
Displacement	10.3 L
Aspiration	Turbocharged aftercooled
Fuel · 100%	2397 CFH
3φ voltage	480/277, 240/120, 240/139, 208/120, 600/346
Motor start	629 sKVA
Dimensions	117.5"×63"×72"
Dry weight	3,924 lb
Sound @ 7 m	70–75 dBA

DIESEL

OLYMPIAN OD20

20 KW

Cat C2.2 · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 & 125 Temp Rise Alternator options
- UL2200, NFPA 110
- EPA Tier 4i Emissions Certificate

SPECIFICATIONS

Standby	20 kW
Engine	Cat C2.2
Displacement	2.2 L

DIESEL

OLYMPIAN OD25

25 KW

Cat C2.2 In-line 4, 4-cycle Diesel · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 & 125 Temp Rise Alternator options
- UL2200, NFPA 110
- EPA Tier 4i Emissions Certificate

SPECIFICATIONS

Standby	25 kW
Engine	Cat C2.2 In-line 4, 4-cycle Diesel
Displacement	2.2 L
Aspiration	Turbocharged
Fuel · 100%	2.45 gal/hr
1φ voltage	240/120
3φ voltage	208/120, 480/277, 600/346, 240/120
Motor start	76 sKVA
Dimensions	59"×38"×46"
Dry weight	1,098 lb

DIESEL

OLYMPIAN OD30

30 KW

Cat C2.2 In-line 4, 4-cycle Diesel · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 105 & 125 Temp Rise Alternator options
- UL2200, NFPA 110
- EPA Tier 4i Emissions Certificate

SPECIFICATIONS

Standby	30 kW
Engine	Cat C2.2 In-line 4, 4-cycle Diesel
Displacement	2.2 L
Aspiration	Turbocharged air to air charge cooling
Fuel · 100%	2.59 gal/hr
1φ voltage	240/120
3φ voltage	208/120, 480/277, 600/346, 240/120
Motor start	76 sKVA
Dimensions	62"×38"×47"
Dry weight	1,349 lb

DIESEL

OLYMPIAN OD40

40 KW

Cat C4.4 In-line 4, 4-cycle Diesel · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate

SPECIFICATIONS

Standby	40 kW
Engine	Cat C4.4 In-line 4, 4-cycle Diesel
Displacement	4.4 L
Aspiration	Turbocharged
Motor start	128 sKVA
Dimensions	77.2"×43.3"×48.0"
Dry weight	1,847 lb
Sound @ 7 m	67.7 dBA

DIESEL

OLYMPIAN OD50

50_{KW}

Cat C4.4 In-line 4, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	50 kW
Engine	Cat C4.4 In-line 4, 4-cycle Diesel
Displacement	4.4 L
Aspiration	Turbocharged
Motor start	197 sKVA
Dimensions	77.2"×43.3"×48.0"
Dry weight	2,055 lb
Sound @ 7 m	68.6 dBA

DIESEL

OLYMPIAN OD60

60_{KW}

Cat C4.4 In-line 4, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	60 kW
Engine	Cat C4.4 In-line 4, 4-cycle Diesel
Displacement	4.4 L
Aspiration	Turbocharged
Motor start	276 sKVA
Dimensions	77.2"×43.3"×48.0"
Dry weight	2,054 lb
Sound @ 7 m	69.6 dBA

DIESEL

OLYMPIAN OD80

80 KW

Cat C4.4 In-line 4, 4-cycle Diesel · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate

SPECIFICATIONS

Standby	80 kW
Engine	Cat C4.4 In-line 4, 4-cycle Diesel
Displacement	4.4 L
Aspiration	Turbocharged
Motor start	328 sKVA
Dimensions	82.6"×43.3"×52.9"
Dry weight	2,095 lb
Sound @ 7 m	76.5 dBA

DIESEL

OLYMPIAN OD100

100 KW

Cat C4.4 In-line 4, 4-cycle Diesel · GCCP 1.2



FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate

SPECIFICATIONS

Standby	100 kW
Engine	Cat C4.4 In-line 4, 4-cycle Diesel
Displacement	4.4 L
Aspiration	Turbocharged
Motor start	328 sKVA
Dimensions	82.6"×43.3"×52.9"
Dry weight	2,222 lb
Sound @ 7 m	76.4 dBA

DIESEL

OLYMPIAN OD125

125 KW

Cat C7.1 In-line 6, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 & 105 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	125 kW
Engine	Cat C7.1 In-line 6, 4-cycle Diesel
Displacement	7.01 L
Aspiration	Turbocharged air to air aftercooled
Fuel · 100%	9.7 gal/hr
Motor start	326 sKVA
Dimensions	103.7"×51.2"×55.2"
Dry weight	3,099 lb
Sound @ 7 m	74.8 dBA

DIESEL

OLYMPIAN OD150

150 KW

Cat C7.1 In-line 6, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 & 105 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	150 kW
Engine	Cat C7.1 In-line 6, 4-cycle Diesel
Displacement	7.01 L
Aspiration	Turbocharged air to air aftercooled
Fuel · 100%	10.0 gal/hr
Motor start	625 sKVA
Dimensions	103.7"×51.2"×55.2"
Dry weight	3,443 lb
Sound @ 7 m	75.4 dBA

DIESEL

OLYMPIAN OD175

175 KW

Cat C7.1 In-line 6, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 & 105 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	175 kW
Engine	Cat C7.1 In-line 6, 4-cycle Diesel
Displacement	7.01 L
Aspiration	Turbocharged air to air aftercooled
Fuel · 100%	13.5 gal/hr
Motor start	738 sKVA
Dimensions	103.7"×51.2"×58.7"
Dry weight	3,741 lb
Sound @ 7 m	79.3 dBA

DIESEL

OLYMPIAN OD200

200 KW

Cat C7.1 In-line 6, 4-cycle Diesel · GCCP 1.2

FEATURES

- Steel enclosed 60 Hz diesel generator set with 24-hour UL listed integral fuel tank
- Emergency Standby Rating
- Single or Three phase options
- 208, 480, 600 & 240 Voltage offerings
- 130 & 105 Temp Rise Alternator
- UL2200, NFPA 110
- EPA Tier 3 Emissions Certificate



SPECIFICATIONS

Standby	200 kW
Engine	Cat C7.1 In-line 6, 4-cycle Diesel
Displacement	7.01 L
Aspiration	Turbocharged air to air aftercooled
Fuel · 100%	14.9 gal/hr
Motor start	780 sKVA
Dimensions	103.7"×51.2"×58.7"
Dry weight	3,917 lb
Sound @ 7 m	79.5 dBA